



# **Supported Environments Guide**

## **Version 9.3.0**

# Copyrights and Trademark Notices

Copyright © 2024 Telestream, LLC and its Affiliates. All rights reserved. No part of this publication may be reproduced, transmitted, transcribed, altered, or translated into any languages without written permission of Telestream, LLC. Information and specifications in this document are subject to change without notice and do not represent a commitment on the part of Telestream. Specifications subject to change without notice.

Telestream, Aurora, CaptionMaker, CaptureVU, Cerify, Content Manager, ContentCentral, Cricket, DIVA, DIVAdirector, DIVADocs, DIVAGrid, DIVANet, DIVAProtect, DIVASolutions, Episode, Encoding Intelligence, Episode, FLEXVU, Flip4Mac, FlipFactory, Flip Player, Geminus, Glim, GraphicsFactory, Inspector, IQ & Design, Kumulate, Lightspeed, MassStore, MassTech, MetaFlip, Post Producer, Prism, ScreenFlow, Sentry, Singulus, Split-and-Stitch, Stay Genlock, Surveyor, Tempo, TrafficManager, Vantage, Vantage Cloud Port, VOD Producer, and Wirecast are registered trademarks of Telestream, LLC and its Affiliates and its Affiliates.

Argus, ContentAgent, Cricket, e-Captioning, Inspector, iQ, iVMS, iVMS ASM, MacCaption, Pipeline, Switch, and Vidchecker are trademarks of Telestream, LLC and its Affiliates. All other trademarks are the property of their respective owners.

**Adobe.** Adobe® HTTP Dynamic Streaming Copyright © 2014 Adobe Systems. All rights reserved.

**Apple.** QuickTime, MacOS X, and Safari are trademarks of Apple, Inc. Bonjour, the Bonjour logo, and the Bonjour symbol are trademarks of Apple, Inc.

**Avid.** Portions of this product Copyright 2012 Avid Technology, Inc.

**CoreOS.** Developers of ETCD.

**Dolby.** Dolby and the double-D symbol are registered trademarks of Dolby Laboratories Licensing Corporation.

**Fraunhofer IIS and Thomson Multimedia.** MPEG Layer-3 audio coding technology licensed from Fraunhofer IIS and Thomson Multimedia.

**Google.** VP6 and VP8 Copyright Google Inc. 2014 All rights reserved.

**MainConcept.** MainConcept is a registered trademark of MainConcept LLC and MainConcept AG. Copyright 2004 MainConcept Multimedia Technologies.

**Manzanita.** Manzanita is a registered trademark of Manzanita Systems, Inc.

**MCW.** HEVC Decoding software licensed from MCW.

**MedialInfo.** Copyright © 2002-2013 MediaArea.net SARL. All rights reserved.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL,

EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

**Microsoft.** Microsoft, Windows NT|2000|XP|XP Professional|Server 2003|Server 2008 |Server 2012|Server 2016|Server 2019|Server 2022, Windows 7, Windows 8, Windows 10, Windows 11, Media Player, Media Encoder, .Net, Internet Explorer, SQL Server 2005|2008|2012|2016|2019, and Windows Media Technologies are trademarks of Microsoft Corporation.

**NLOG, MIT, Apache, Google.** NLog open source code used in this product under MIT License and Apache License is copyright © 2014-2016 by Google, Inc., © 2016 by Stabzs, © 2015 by Hiro, Sjoerd Tieleman, © 2016 by Denis Pushkarev, © 2015 by Dash Industry Forum. All rights reserved.

**SharpSSH2.** SharpSSH2 Copyright (c) 2008, Ryan Faircloth. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer:

Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

Neither the name of Diversified Sales and Service, Inc. nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

**Swagger.** Licensed from SmartBear.

**Telerik.** RadControls for ASP.NET AJAX copyright Telerik All rights reserved.

**VoiceAge.** This product is manufactured by Telestream under license from VoiceAge Corporation.

**x264 LLC.** The product is manufactured by Telestream under license from x264 LLC.

**Xceed.** The Software is Copyright ©1994-2012 Xceed Software Inc., all rights reserved.

**ZLIB.** Copyright (C) 1995-2013 Jean-loup Gailly and Mark Adler.



Other brands, product names, and company names are trademarks of their respective holders, and are used for identification purpose only.

## MPEG Disclaimers

### MPEGLA MPEG2 Patent

ANY USE OF THIS PRODUCT IN ANY MANNER OTHER THAN PERSONAL USE THAT COMPLIES WITH THE MPEG-2 STANDARD FOR ENCODING VIDEO INFORMATION FOR PACKAGED MEDIA IS EXPRESSLY PROHIBITED WITHOUT A LICENSE UNDER APPLICABLE PATENTS IN THE MPEG-2 PATENT PORTFOLIO, WHICH LICENSE IS AVAILABLE FROM MPEG LA, LLC, 4600 S. Ulster Street, Suite 400, Denver, Colorado 80237 U.S.A.

### MPEGLA MPEG4 VISUAL

THIS PRODUCT IS LICENSED UNDER THE MPEG-4 VISUAL PATENT PORTFOLIO LICENSE FOR THE PERSONAL AND NON-COMMERCIAL USE OF A CONSUMER FOR (i) ENCODING VIDEO IN COMPLIANCE WITH THE MPEG-4 VISUAL STANDARD (“MPEG-4 VIDEO”) AND/OR (ii) DECODING MPEG-4 VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL AND NON-COMMERCIAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION INCLUDING THAT RELATING TO PROMOTIONAL, INTERNAL AND COMMERCIAL USES AND LICENSING MAY BE OBTAINED FROM MPEG LA, LLC. SEE [HTTP://WWW.MPEGLA.COM](http://www.mpegla.com).

### MPEGLA AVC

THIS PRODUCT IS LICENSED UNDER THE AVC PATENT PORTFOLIO LICENSE FOR THE PERSONAL USE OF A CONSUMER OR OTHER USES IN WHICH IT DOES NOT RECEIVE REMUNERATION TO (i) ENCODE VIDEO IN COMPLIANCE WITH THE AVC STANDARD (“AVC VIDEO”) AND/OR (ii) DECODE AVC VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED TO PROVIDE AVC VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR

ANY OTHER USE. ADDITIONAL INFORMATION MAY BE OBTAINED FROM MPEG LA, L.L.C. SEE [HTTP://WWW.MPEGLA.COM](http://www.mpegla.com).

## MPEG4 SYSTEMS

THIS PRODUCT IS LICENSED UNDER THE MPEG-4 SYSTEMS PATENT PORTFOLIO LICENSE FOR ENCODING IN COMPLIANCE WITH THE MPEG-4 SYSTEMS STANDARD, EXCEPT THAT AN ADDITIONAL LICENSE AND PAYMENT OF ROYALTIES ARE NECESSARY FOR ENCODING IN CONNECTION WITH (i) DATA STORED OR REPLICATED IN PHYSICAL MEDIA WHICH IS PAID FOR ON A TITLE BY TITLE BASIS AND/OR (ii) DATA WHICH IS PAID FOR ON A TITLE BY TITLE BASIS AND IS TRANSMITTED TO AN END USER FOR PERMANENT STORAGE AND/OR USE. SUCH ADDITIONAL LICENSE MAY BE OBTAINED FROM MPEG LA, LLC. SEE [HTTP://WWW.MPEGLA.COM](http://www.mpegla.com) FOR ADDITIONAL DETAILS.

## Limited Warranty and Disclaimers

Telestream, LLC (the Company) warrants to the original registered end user that the product will perform as stated below for a period of one (1) year from the date of shipment from factory:

*Hardware and Media*—The Product hardware components, if any, including equipment supplied but not manufactured by the Company but NOT including any third party equipment that has been substituted by the Distributor for such equipment (the “Hardware”), will be free from defects in materials and workmanship under normal operating conditions and use.

## Warranty Remedies

Your sole remedies under this limited warranty are as follows:

*Hardware and Media*—The Company will either repair or replace (at its option) any defective Hardware component or part, or Software Media, with new or like new Hardware components or Software Media. Components may not be necessarily the same, but will be of equivalent operation and quality.

## Software Updates

Except as may be provided in a separate agreement between Telestream and You, if any, Telestream is under no obligation to maintain or support the Software and Telestream has no obligation to furnish you with any further assistance, technical support, documentation, software, update, upgrades, or information of any nature or kind.

## Restrictions and Conditions of Limited Warranty

This Limited Warranty will be void and of no force and effect if (i) Product Hardware or Software Media, or any part thereof, is damaged due to abuse, misuse, alteration,

neglect, or shipping, or as a result of service or modification by a party other than the Company, or (ii) Software is modified without the written consent of the Company.

## Limitations of Warranties

THE EXPRESS WARRANTIES SET FORTH IN THIS AGREEMENT ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. No oral or written information or advice given by the Company, its distributors, dealers or agents, shall increase the scope of this Limited Warranty or create any new warranties.

**Geographical Limitation of Warranty**—This limited warranty is valid only within the country in which the Product is purchased/licensed.

**Limitations on Remedies**—YOUR EXCLUSIVE REMEDIES, AND THE ENTIRE LIABILITY OF TELESTREAM, LLC WITH RESPECT TO THE PRODUCT, SHALL BE AS STATED IN THIS LIMITED WARRANTY. Your sole and exclusive remedy for any and all breaches of any Limited Warranty by the Company shall be the recovery of reasonable damages which, in the aggregate, shall not exceed the total amount of the combined license fee and purchase price paid by you for the Product.

## Damages

TELESTREAM, LLC SHALL NOT BE LIABLE TO YOU FOR ANY DAMAGES, INCLUDING ANY LOST PROFITS, LOST SAVINGS, OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF YOUR USE OR INABILITY TO USE THE PRODUCT, OR THE BREACH OF ANY EXPRESS OR IMPLIED WARRANTY, EVEN IF THE COMPANY HAS BEEN ADVISED OF THE POSSIBILITY OF THOSE DAMAGES, OR ANY REMEDY PROVIDED FAILS OF ITS ESSENTIAL PURPOSE.

Further information regarding this limited warranty may be obtained by writing:  
Telestream, LLC  
848 Gold Flat Road  
Nevada City, CA 95959 USA

You can call Telestream during U. S. business hours via telephone at (530) 470-1300.

## Regulatory Compliance

Electromagnetic Emissions: FCC Class A, EN 55022 Class A, EN 61000-3-2/-3-3, CISPR 22 Class A

Electromagnetic Immunity: EN 55024/CISPR 24, (EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11)

Safety: CSA/EN/IEC/UL 60950-1 Compliant, UL or CSA Listed (USA and Canada), CE Marking (Europe)

California Best Management Practices Regulations for Perchlorate Materials:  
 This Perchlorate warning applies only to products containing CR (Manganese Dioxide)  
 Lithium coin cells. Perchlorate Material-special handling may apply. See  
[www.dtsc.ca.gov/hazardouswaste/perchlorate](http://www.dtsc.ca.gov/hazardouswaste/perchlorate).

## Obtaining Support | Information | Assistance

Contact Telestream for support, information or assistance, as indicated below.

Resource	Contact Information
DIVA Technical Support   Information   Assistance   FAQ   Forums   Upgrades	Web site: <a href="http://telestream.net/telestream-support/DIVA/support.htm">telestream.net/telestream-support/DIVA/support.htm</a> Web site: <a href="http://telestream.net/telestream-support/DIVA/support.htm">telestream.net/telestream-support/DIVA/support.htm</a> Support Email: <a href="mailto:support@telestream.net">support@telestream.net</a> US Phone: 877-257-6245 International Phone: +1 530-470-2036 Support hours: Monday - Friday, 7am - 6pm Pacific time. P1 Support: 24 x 7. Terms and times of support services vary, per the terms of your service contract with Telestream. Depending on problem severity, Telestream responds within 24 business hours. For P1 issues, Telestream responds within one hour.
Product Licensing	Web site: <a href="http://telestream.net/telestream-support/DIVA/support.htm">telestream.net/telestream-support/DIVA/support.htm</a> License Email: <a href="mailto:license@telestream.net">license@telestream.net</a>
Telestream, generally	Web site: <a href="http://telestream.net">telestream.net</a> Sales and Marketing Email: <a href="mailto:info@telestream.net">info@telestream.net</a>
Telestream Reseller Support	If you purchased your product from a reseller, please contact your reseller for support.
International Reseller Support	Website: <a href="http://telestream.net">telestream.net</a> See the Telestream website for your regional authorized Telestream reseller.
Telestream Technical Writers	Email: <a href="mailto:techwriter@telestream.net">techwriter@telestream.net</a> If you have comments or suggestions about improving this document or other Telestream documents—or if you've discovered an error or omission, please email us.

## DIVA Library

For more information about DIVA, browse the DIVA library at [telestream.net/telestream-support/DIVA/support.htm](https://telestream.net/telestream-support/DIVA/support.htm).



# Supported Environments

This chapter provides setup details for environments that DIVA supports. It also provides details for architecture and server-sizing purposes.

## Topics

- [Overview](#)
- [Core Options and Licensing Metrics](#)
- [Product Compatibility](#)
- [Hardware and Software Requirements](#)
- [Supported Libraries and Control Software](#)
- [Supported Drives](#)
- [Supported Disks](#)
- [Supported Object Storage](#)
- [Supported Partial File Restore Formats](#)
- [Supported Unmanaged Storage Repositories](#)
- [Supported Transcoders](#)
- [Supported Avid Environments](#)

## Overview

The DIVA architecture allows the integration of many different types of servers and technologies, such as Broadcast Video Servers, Storage Area Networks, and Enterprise Tape Group Managed Storage. DIVA can support interoperability among systems, helping to ensure long term accessibility to valued content, and keeping up with evolving storage technologies.

DIVA supports system installations in Windows 2016, 2019, and 2022. All Windows installations must be in English only.

The installation of DIVA varies from site to site. The exact configuration of your specific DIVA platform is not covered in this guide. For details on your specific DIVA System

installation and configuration, consult with the Telestream Installation and Delivery Team.

---

**Note:** Telestream recommends keeping the operating system up to date with the latest security patches.

---

## Core Options and Licensing Metrics

The following table identifies Core options and licensing metrics.

Description	Licensing Metric
DIVA System	Per Server
DIVA Single	Per Server
DIVA Actor	Per Server
DIVA Avid Connector	Per Avid Archive Provider
DIVA Partial File Restore	Per System
DIVA Analytics	Per Server
Managed Storage Capacity	Per 500 TB Block
Unlimited Storage Capacity	Per System

## Product Compatibility

DIVA is compatible with other DIVA Core product lines including the following:

### Postgres Database and DIVA Backup Service

The Database and Backup Service components are installed as integral parts of the standard DIVA system installation; typically on the same server as DIVA.

Scheduled backups using the DIVA Backup Service are configured in its configuration file. The DIVA Backup Service manages and monitors the entire backup process. DIVA supports Postgres Database version 14.

The DIVA Backup Service is also used to backup the MongoDB database and Elasticsearch, which are both required for metadata storage and searching.

### DIVA Connect

DIVA Connect 4.0 supports DIVA 8.0, 8.1, 8.3, 9.0 and above. DIVA Connect 4.0 works with DIVA API versions 9.0 and below. The DIVA Connect 4.0 ClientAdapter doesn't inter-operate with the DIVA Connect Core Adapter 3.2 and below. Either DIVA Connect 2.0 or Legacy DIVA Connect must be used when running DIVA Core releases earlier than DIVA Core 7.3.1.

If operating a DIVA Core release earlier than 7.3.1, refer to the *DIVA Connect Installation, Configuration, and Operations Guide*.

## FlashNet to DIVA Migration

---

**Note:** For information about upgrading from FlashNet to DIVA, contact Telestream Support.

---

FlashNet customers can upgrade to DIVA or Kumulate while keeping their yearly payments at the same price as their existing support fees. While the FlashNet licenses will be transferred over at no cost, a modest one-time surcharge will be applied for the professional services needed for the upgrade.

Customers can trade-in their existing FlashNet licenses for either subscription or perpetual licenses. For customers who choose subscription licensing, any content written to storage will continue to be accessible even if that subscription were to lapse.

This upgrade is designed to use the FlashNet-written archives on their existing media, so that customers can avoid a time-consuming media migration.

## Supported API Releases

The following legacy API releases and configurations are supported for each major DIVA Core and DIVA release. That is, the last two version-number changes.

---

**Note:** Telestream has deprecated the DIVA C++ API and the DIVA Java API.

---

**Note:** Telestream strongly recommends that you use the DIVA REST API rather than previous APIs such as the DIVA C++ API. The DIVA C++ API is deprecated, but supported for backward compatibility. The DIVA REST API offers new and enhanced features and security.

---

### DIVA REST API

DIVA exposes its functionality through a REST interface. It is self-contained in DIVA and all future DIVA releases. The API is used by the DIVA Web App and other internal components (for example, SPM, Migration Service, and so on).

For detailed information, see the *DIVA Application Programming Guide*.

### Web Services APIs

- DIVA REST API: the DIVA REST API is embedded in DIVA.
- WS 2.1: REST and SOAP require the DIVAS component. (Deprecated)
- WS 2.2: REST and SOAP require the DIVA Enterprise Connect component. (Deprecated)

## Supported and Tested Legacy API Configurations

The following API configurations are supported in DIVA and later:

- DIVA C++ API 7.5 to 5.5 on Windows
- DIVA Java API 7.5 to 6.5 on Windows
- Enterprise Connect (latest release) on Windows with the following configurations:
  - http, rest, xml, connect directly to DIVA
  - http, rest, form\_url\_encoded, connect directly to DIVA
  - http, soap, xml, connect directly to DIVA
  - https, rest, xml, connect directly to DIVA
  - https, rest, form\_url\_encoded, connect directly to DIVA
  - https, soap, xml, connect directly to DIVA

## Untested Configurations

The following API configurations are untested. Use them at your own risk:

- C++ and Java Legacy API 7.6 and newer.
- DIVA Core Symphony; that is, DIVAS that uses WSO2 application server.
- Older Enterprise Connect (older than latest release). That is, if another EC is released, only the latest release will be tested.
- Enterprise Connect connected using the DIVA Core Adapter mode.

# Hardware and Software Requirements

These are the minimum hardware and software requirements to install and operate the DIVA software. Refer to [General Storage Requirements](#) for detailed disk configuration information.

---

**Note:** MongoDB, in its default configuration, can use up to half the available RAM minus 1GB on the server on which it is installed. You have to plan the location of MDS MongoDB installation accordingly.

---

## DIVA Architecture

A DIVA system uses a combination of software modules which can run on a single computer, or can be distributed across different systems.

The main DIVA components are as follows:

### Manager

The DIVA component of the archive also hosting the archive system database.

## Manager Cluster

Based on the Microsoft Cluster configuration. Manager Cluster is valid only in a Windows-based environment.

## Actor

Responsible for all data transfers to storage media (Archive, Restore, Copy, Repack, and so on).

## Actor and Manager (Single Computer)

Systems running both Actor and Manager functions on a single computer. Try to avoid this configuration for performance reasons. This is only usable for entry level configurations.

## DIVA Connect 2.1 and later

Used in DIVA Connect configurations for unified access. DIVA Connect 2.1 (and later) is not a drop in replacement for the legacy DIVA Connect. DIVA Connect 2.1 (and later) is specifically for compatibility with DIVA Core 7.5 and later Linux and Windows installations, and not backward compatible with earlier DIVA Core releases before 7.3.1.

---

**Note:** DIVA Connect 4.0 has been released with DIVA.

---

See the DIVA Connect documentation on the Telestream DIVA Support Portal for detailed DIVA Connect information.

## DIVA Web App


Used for configuring, monitoring and managing the DIVA system.

---

**Note:** Telestream recommends using the Chrome browser to use the DIVA Web App.

---

The following figure represents a DIVA configuration with the main DIVA software components installed on different servers. DIVA Connect (used to access multiple DIVA systems) is not represented and is generally installed on a dedicated server.



## System Component Interconnectivity

On the data path, a DIVA solution is connected on the storage side to the Tape Group library, shared disks, Object Storage, or any combination of these. On the source and target side, it is connected to the video servers, nonlinear editors, or file servers.

### Storage Connection

SAN (Storage Area Networks), NAS (Network Attached Storage), or Direct Attached technologies can be used. Different types of interfaces are required on the servers to support the different types of storage devices as follows:

- Fiber Channel HBA (Host Based Adapter) for SAN
- SCSI Bus or HBA for Direct Attach
- 10 Gigabit Ethernet for NAS
- Cloud Storage
- Tape Libraries

## Intel and Microsoft Windows

Telestream can deliver x86 architecture servers matching or exceeding the recommendations provided in the following sections (except the Windows license to be purchased). Partners can also purchase servers from other vendors if the minimum requirements are met. Telestream does not qualify or recommend specific models from other vendors.

---

**Note:** The operating system installed on all computers must be installed in the English language. Telestream does not support DIVA computers that have the operating system installed in other languages.

---

## DIVA Appliance

The DIVA appliance is a pre-built system available to customers that includes hardware and software ready to rack and turn on.

The appliance is supported by the DIVA installer and creates a site-production system that includes some arrays to match the expected hardware. There is currently no special implementation in the DIVA Web App for the appliance at this time.

Telestream has generated a wizard on startup to guide customers through importing a license, along with any other configuration required; this has not been implemented at this time.

## Operating System Compatibility

Use the following table to confirm that you have the proper operating system installed for each computer in the system when upgrading your DIVA installation.

---

**Note:** The minimum server operating system for using complex objects is Windows Server 2016.

---

Component	DIVA Release	Operating System Compatibility (for upgrades only)
DIVA and Actor	9.0 and later	Windows Server 2016 Windows Server 2019 Windows Server 2022
DIVA Connect	2.3.1 and later	Windows Server 2016 Windows Server 2019 Windows Server 2022 Oracle Linux 7 x86_64 and later (64-bit)

## Manager

HDD sizing for the Manager is now more complex. With the addition of MongoDB, Elasticsearch, and Postgres, more space is required for successful operations. The following server platform is the minimum requirement recommended for the installation of the Manager software:

- Rack mount chassis
- Intel® Xeon® Silver 4214R 2.4Ghz 12C/24T or equivalent (optional second processor possible)

- 64GB RAM
- Two 2 TB HDD 15,000 RPM or SSD (configured in RAID 1) system disks (and an optional third disk used as a hot spare)

---

**Note:** If DIVA is used to archive complex objects like DPX or Avid sequences, it is advisable to ask for a specific recommendation based on the estimated traffic (in terms of size and number of objects to be archived per day). In general, if complex objects need to be archived, Telestream recommends using a minimum of two 2 TB HDD with 15,000 RPM. This recommendation is also valid for the Backup Manager or an Actor if an Actor server is used for the Backup Manager.

---

- Redundant power supply and fans
- Dual on-board GbE or 10GbE interfaces (copper RJ45 interfaces)
- Dual port 16Gb Fiber Channel HBA (Host Bus Adapter) for Tape library control (only if a tape library is used and requires the use of a dedicated FC connection)
- Windows Server 2016
- Windows Server 2019
- Windows Server 2022

See the [Minimum Partition Sizing for a Server Hosting Databases](#) table.

## Manager Cluster

---

**Note:** DIVA 9.3 has not been tested with clusters.

---

The following server platform (two identical servers) is the minimum requirement recommended for the installation of the Manager software in a cluster environment. A Manager Cluster is only valid in a Windows-based environment.

- Rack mount chassis
- One Intel® Xeon® Silver 4214R 2.4Ghz 12C/24T or equivalent (optional second processor possible)
- 64GB RAM
- Two 2TB HDD 15,000 RPM or SSD (configured in RAID 1) system disks (and an optional third disk used as a hot spare)

---

**Note:** If DIVA is used to archive complex objects like DPX or Avid sequences, it is advisable to ask for a specific recommendation based on the estimated traffic (in terms of size and number of objects to be archived per day). In general, if complex objects need to be archived, Telestream recommends using a minimum of two 2TB HDD with 15,000 RPM. This recommendation is also valid for the Backup Manager or an Actor if an Actor server is used for the Backup Manager.

---



- Redundant power supply and fans
- Two on-board GbE or 10GbE interfaces (copper RJ45 interfaces)
- Dual port SAS or FC HBA (for the shared disk bay connection)

---

**Note:** A shared disk bay with dual RAID controller (SAS or FC Interface) and seven 300 GB SAS disks connected to both servers to accommodate the database.

---

- Dual port 16Gb Fiber Channel HBA for Tape library control (only if a tape library is used and requires the use of a dedicated FC connection)
- Windows Server 2016
- Windows Server 2019
- Windows Server 2022

See the [Minimum Partition Sizing for a Server Hosting Databases](#) table.

## Actor

The following is the minimum server configuration recommended for the installation of the Actor software:

- Rack mount chassis
- One Intel® Xeon® Silver 4214R 2.4Ghz 12C/24T or equivalent
- 32GB RAM
- Two 300 GB HDD 15,000 RPM or SSD (configured in RAID1) system disks (optional third disk can be used as a hot spare)
- RAID5 disk space for cache, at least five 1.8TB disks
- Optional RAID5 disk space for Nearline storage (DIVAgrid Architecture)

---

**Note:** The DIVAgrid Architecture consists of aggregating direct attached disks from multiple Actors into one single DIVA array. The Manager distributes content it needs to store on this array across the different Actors composing the array. This provides a cost-effective, high performance solution for Nearline disk storage and is ideal in workflows requiring temporary disk storage to enable the creation of multiple object instances and transcoding.

---

- Redundant power supply and fans
- Two on-board GbE interfaces (copper RJ45 interfaces)
- Dual 10 GbE ports interface
- Dual port Fiber Channel HBA for the connection to an external shared SAN disk (optional)
- Dual port Fiber Channel HBA for the connection to the Tape drives (Qlogic recommended)
- Windows Server 2016

- Windows Server 2019
- Windows Server 2022

See the [Minimum Partition Sizing for a Server Hosting Databases](#) table.

### Actor and Manager (Single Computer)

The following is the minimum server configuration recommended for the installation of the Actor and Manager software on a single computer. This configuration should be limited to entry level systems for performances reasons:

- Rack mount chassis
- One Intel® Xeon® Silver 4214R 2.4Ghz 12C/24T or equivalent (optional second processor possible)
- 64GB RAM
- Two 2TB HDD 15,000 RPM (configured in RAID1) system disks (optional third disk can be used as a hot spare)

---

**Note:** If DIVA is used to archive complex objects like DPX or Avid sequences, it is advisable to ask for a specific recommendation based on the estimated traffic (in terms of size and number of objects to be archived per day). In general, if complex objects need to be archived, Telestream recommends using a minimum of two 900 GB HDD with 15,000 RPM. This recommendation is also valid for the Backup Manager or an Actor if an Actor server is used for the Backup Manager.

---

- RAID5 disk space—at least five 2TB disks, Redundant power supply, and fans
- Two on-board GbE interfaces
- Two 10 GbE interface (optional)
- Dual port Fiber Channel HBA for the connection to an external shared SAN disk (optional)
- Dual port 16Gb Fiber Channel HBA for the connection to Tape drives (Qlogic recommended)
- Windows Server 2016
- Windows Server 2019
- Windows Server 2022

See the [Minimum Partition Sizing for a Server Hosting Databases](#) table.

### DIVA Connect 4.x

The DIVA Connect configuration provides a consolidated view of a distributed DIVA system. The following is the minimum server configuration recommended for the installation of DIVA Connect 4.x:

- Rack mount chassis

- One Intel® Xeon® Silver 4214R 2.4Ghz 12C/24T or equivalent
- 64GB RAM
- Two 480GB HDD 15,000 (configured in RAID1) system disks (optional third disk can be used as a hot spare)
- One 10 GbE interfaces (optional)
- Oracle Linux 7 x86\_64 and later
- Windows Server 2016
- Windows Server 2019
- Windows Server 2022

See the DIVA Connect documentation on the Telestream DIVA Support Portal for detailed DIVA Connect information.

## General Storage Requirements

The following table describes the main storage characteristics of the various components:

Server	CPU	System Disks	Cache and Disk	Data Disks
Manager Cluster <sup>1</sup>	1	RAID1	No	No
Manager	1	RAID1	No	No
Actor	1	RAID1	RAID5	Nearline (optional)
Actor and Manager	1	RAID1	RAID5	Nearline (optional)
Actor and Transcoder	2	RAID1	RAID5	Transcoding area plus optional Nearline disk.
DIVA Connect	1	RAID1	No	No

1. Manager Cluster is valid only in a Windows-based environment.

### Minimum Partition Sizing for a Server Hosting Databases

The following are the minimum partition sizes for the Manager computer. These minimum sizes are also valid for a Manager Backup configuration or an Actor used as a Backup Manager.

Different sizing requirements may apply depending on your DIVA production workflow. For example, extensive use of Metadata, generation of proxies, the use of Complex Objects have an impact on the volume of data stored in the databases used by DIVA. Contact Telestream Support if you have questions specific to your workflow and Partitions Sizing.

The Postgres database has these minimum requirements:

- Windows 2016 or higher

- 16 GB of RAM

---

**Caution: All partitions must be protected by RAID.**

---

<b>Windows Partition</b>	<b>Minimum Size</b>	<b>Recommended Block Size</b>	<b>Comments</b>
C:\	200 GB	Operating System Default	DIVA Software including Operating System, DIVA binaries, DIVA operational log files and 3rd party DB engine binaries used by DIVA
E:\	100 GB	8 kb	Database Data Files
F:\	Windows: 50 GB (exactly)	4 kb	Database Archive Logs
H:\	300 GB	64 kb	Database Backup Folder
M:\	100 GB	Operating System Default	MongoDB Metadata Database - used to store normal Object Metadata as well as Complex Objects Metadata
S:\	500 GB	Operating System Default	Elasticsearch Database

## Supported Libraries and Control Software

The following table identifies Managed Storage and associated control software supported by DIVA LibAttach is valid only in a Windows-based environment.

Manufacturer	Library	Control Software	Robot Manager Module
Alto	Disk Library	Alto Protocol	ALTO_Robot.dll
Dell	TL4000/TL2000 <sup>1</sup> ML6010 <sup>2</sup>	Direct SCSI/FC	Robot_SCSI
HP	StoreEver, ESL-G3-700, ESL-G3-1500, ESL-G3-3000, ESL-G3-5000, MSL-2024, MSL-2048, MSL-6480	Direct SCSI/FC	Robot_SCSI
IBM	TS3100, TS3200, TS3310, TS3500, TS4500	Direct SCSI/FC	Robot_SCSI
Oracle StorageTek	SL8500 <sup>3</sup> SL500 <sup>4</sup> SL150 9310 5500 L180  L7000 SL24 L80 L40 L20 L1400M	LibAttach 1.4.2 <sup>5</sup> Direct SCSI/FC Direct SCSI/FC ACSL S ACSL S ACSL S or Direct SCSI/FC  ACSL S LibAttach 1.4.2 <sup>5</sup> Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC	Robot_ACSLS Robot_SCSI Robot_SCSI Robot_ACSLS Robot_ACSLS Robot_ACSLS or Robot_SCSI  Robot_ACSLS Robot_ACSLS Robot_ACSLS Robot_ACSLS Robot_ACSLS
Oracle StorageTek	SL4000	LibAttach 1.4.25 Direct SCSI/FC	Robot_ACSLS Robot_SCSI

<b>Manufacturer</b>	<b>Library</b>	<b>Control Software</b>	<b>Robot Manager Module</b>
Oracle StorageTek	SL3000	LibAttach 1.4.25 Direct SCSI/FC	Robot_ACSL5 Robot_SCSI
Overland Tandberg	NEO XL Series	Direct SCSI/SAS	Robot_SCSI
Qualstar	TLS-5000 RLS-85210 Q series	Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC	Robot_SCSI Robot_SCSI Robot_SCSI
Quantum (ADIC)	Scalar i6000 Scalar i500 Scalar i40/i80 Scalar i3/i6 Scalar 100  Scalar 1000  Scalar 10000  Scalar 12000  Scalar i2000 <sup>6</sup>	Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC Scalar DLC or Direct SCSI/FC  Scalar DLC or Direct SCSI/FC  Scalar DLC or Direct SCSI/FC  Scalar DLC or Direct SCSI/FC  Scalar DLC or Direct SCSI/FC	Robot_SCSI Robot_SCSI Robot_SCSI Robot_SCSI Robot_ADIC or Robot_SCSI  Robot_ADIC or Robot_SCSI  Robot_ADIC or Robot_SCSI  Robot_ADIC or Robot_SCSI
Sony Petasite	S60	PSC 5.00	Robot_Sony
Sony ODA	ODS-L10 ODS-L30M ODS-L60E ODS-L100E	Core Robot Manager Core Robot Manager Core Robot Manager Core Robot Manager	Robot_SCSI Robot_SCSI Robot_SCSI Robot_SCSI
Spectralogic	T-Finity T950 T680, T380, T200 T120 T50e	Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC Direct SCSI/FC	Robot_SCSI Robot_SCSI Robot_SCSI Robot_SCSI Robot_SCSI
ALTO	ALTO-III ALTO-ARX	ALTO Manager	Robot_ALTO

1. The Dell TL2000 is an IBM TS3100 library.

2. The Dell ML6010 is an AIDC i500 library.
3. Operational upon robot failure when configured with multiple LSMs and one robot per LSM.
4. The SL500 library will be transitioned to End of Life (EOL) soon.
5. DIVA only supports 32-bit LibAttach and not 64-bit.
6. Autoclean is not supported, but the Scalar i2000 with partitioning is supported.

---

**Note:** The latest qualified release of ACSLS is 8.5.1.

---

### Disk Archive Corporation ALTO

ALTO is an offline, cold storage archive; a secure and convenient alternative to data tape, optical disk, and cloud for Petabyte sized volumes of valuable media assets. ALTO uses data file replication to create multiple non-segmented replicas of files on removable media. ALTO systems can be distributed between on-premises and other geographically separated locations. Disks can be bar-coded and externalized to vault storage for air-gap security providing a copy of last resort for disaster recovery.

DIVA supports ALTO storage in two different ways:

- With Virtual File System (VFS), in which case multiple Alto disks are combined and presented by VFS as a Virtual Disk. From the DIVA Web App the storage appears as a DIVA Array.
- Direct API integration, in which case Alto is considered as a removable storage system like tape libraries or Sony ODA. DIVA tracks and exposes the content stored on each disk and groups can be created as with tapes or ODA.

## Supported Drives

The following drives are supported by DIVA.

Manufacturer	Drive Model
HP	LTO-3, LTO-4, LTO-5, LTO-6, LTO-7, LTO-8, LTO-9
IBM	LTO-1, LTO-2, LTO-3, LTO-4, LTO-5, LTO-6, LTO-7 <sup>1</sup> , LTO-8, LTO-9  <b>Note:</b> When a virgin LTO-9 tape is mounted into a drive for the first time, it will require an initialization that may take between 30 minutes and 2 hours. In DIVA, the consequence is the positioning step will take between 30 minutes and 2 hours.  3592 Jaguar TS1120, TS1140, TS1150, TS1155, TS1160
Oracle StorageTek	Titanium 10000-A, 10000-B, 10000-C, 10000-D 9840A, 9840B, 9840C, 9840D, 9940A, 9940B
Sony (Optical)	ODS-D55U, ODS-D77F, ODS-280F, ODS-280U <sup>2</sup> , ODS-D380F

1. Drivers for the IBM LTO-7 and LTO-8 drives only exist for Windows Server 2012.

2. The ODS-280U has not been qualified for use with DIVA.

### Sony ODA Optical Drives

Sony ODA Blu-ray Optical Drives are supported in DIVA on Windows only. To view the drives as a Tape Group Drive and Cartridge (having UDF format) in the DIVA Web App browse to *Resource Management > Drives*.

The drives must be configured using the Optical Disk Archive Utility before configuring DIVA on the system.

The Windows Device Manager will display the drives as an Unknown Device because there are no drivers available for them. Several configuration files must be modified to include these drives in the DIVA System. See the DIVA Installation and Configuration Guide for detailed information.

The details of these drives are as follows:

- DIVA has only been tested with the ODS-280F Fiber Channel type. These drives are twice as fast as the Gen1 drives. The ODS-280U has not been qualified for use with DIVA.
- The cartridge available for the ODC3300R WORM drive has a 3.3 TB capacity.
- Gen2 drives can read content written on Gen1 media with Gen1 drives. DIVA does not support the READ-ONLY media drive compatibility. Telestream recommends isolating Gen1 media from Gen2 media in the configuration (no cross-generation compatibility), and there must be at least one Gen1 drive in a library containing Gen1 cartridges.
- Sony ODA Gen 3 is supported. The drive type is ODS-D380F and uses the following new cartridge:

**–Cartridge Type:**

ODC5500R

**–Capacity**

5.5 TB

**–Drive Type**

WORM

---

**Note:** The drive is still R/W compatible with ODC3300R and read-only compatible with older cartridge types.

---

## Supported Disks

DIVA supports the following disks:

- Direct Connection using a local path
- For example drive letters in Windows such as M:\managed\_disk.
- CIFS Connection



- FTP Connection
- Harmonic MediaGrid
- Tiger MetaSan
- Quantum StoreNext Filesystem
- IBM GPFS (General Purpose Filesystem)
- Huawei OceanStore 9000
- Dell PowerScale (Isilon)

### **Cache Disk**

This disk is only used for caching, Tape Group to Tape Group copying, Tape Group spanning, and Tape Group repacking operations. The cache does not have to be on a RAID protected disk, but it is recommended.

The size of this disk must be at least the size of the largest object. The cache disk can be a local disk, SAN, NFS, or SMB connected. Telestream recommends setting the cache disk block size to at least 64KB.

### **Storage or Storage and Nearline**

The disk will be used for storing objects and Nearline operations. The storage size depends on the amount of space desired to store objects. This disk must be RAID protected.

A storage disk can also be used for cache. The storage disk can be a local disk, SAN, NFS, or SMB connected. Telestream recommends setting the storage disk block size to at least 64KB.

## Supported Object Storage

The following table identifies object storage accounts supported by DIVA.

Object Storage Type	Protocol	Supported Storage Classes	AXF Reference-File	Auto-Indexing	AXF Discovery
Alibaba OSS	S3	Standard, IA (Infrequent Access), Archive, ColdArchive	Yes	Yes	Yes
AWS S3	S3	Standard, Intelligent-Tiering, Standard-IA, One Zone-IA, Glacier, Glacier-Deep-Archive, Glacier-Instant-Retrieval	Yes	Yes	Yes
Azure Blob Storage	Blob REST API	Standard, Hot, Cool, Cold, Archive	Yes	Yes	Yes
Ceph	S3	Standard	Currently Not Tested	Yes	Yes
Cloudian	S3	Standard, Archive	Yes	Yes	Yes
EMC ECS	Swift / S3	Standard	Yes	Yes	Yes
Google Cloud Storage	JSON API	Standard, Nearline, Coldline, Archive	Yes	Yes	Yes
HCP (Hitachi Content Platform)	S3	Standard	Yes	Yes	Yes
Isilon OneFS (8.2 and later)	S3	Standard	Yes	Yes	Yes
NetApp StorageGRID	S3	Standard	Currently Not Tested	Yes	Yes
ObjectMatrix MaxiStore	S3	Standard	Yes	Not currently tested.	Not currently tested.
Oracle Cloud Storage	OCI	Standard, Archive	Yes	No	No

Object Storage Type	Protocol	Supported Storage Classes	AXF Reference-File	Auto-Indexing	AXF Discovery
Scality	S3	Standard	Not Supported Yet	Yes	Yes
Tata Cloud Storage	S3	Standard	Yes	Yes	Yes
Backblaze	S3	Standard	Yes	No	Yes
Wasabi	S3	Standard	Yes	Yes	Yes

### Ceph Implementation Notes

The current Ceph implementation can't create a bucket in Ceph storage due to the Ceph current implementation of the S3 protocol; so the bucket must exist before DIVA can write to it. For use as disk (rather than as a server) the user must provide the bucket to use through the `-bucket_name` option in the *Storage Options* field of the corresponding array definition.

There must be two buckets created prior to using Ceph as a Storage Array: one for data and one for metadata; `mybucket` and `mybucket-metadata`, for example. Create those two buckets. Then, in the *Storage Options* field of the *ADD ARRAY* page, specify `-bucket_name=mybucket`.

### Configuring HCP (Hitachi Content Platform) for Multi-part Upload

To configure HCP for multi-part upload, do the following:

1. Disable the etag verification. To disable etag verification, browse to *Configuration > Resources > CLOUD STORAGE CLOUD BUCKETS*. Set the parameter *Additional Checksum Verification* to *None*.
2. In the HCP Management Console, browse to *Namespace > Settings > Optimization*. Set only the option *Optimized for Cloud Protocols*.

## Supported Partial File Restore Formats

Numerous object formats have been tested successfully with the DIVA Partial File Restore operation. Testing with samples provided by the customer is recommended to confirm interoperability. Telestream makes no commitment if variations in the encoding profiles cause issues with the DIVA Partial File Restore feature. All formats support `AUTO_DETECT`.

To access the Partial File Restore settings in the DIVA Web App, browse to *Configuration > System Settings > Actors > Edit Actor > Partial Restore Settings*.

For details about each implementation, contact Telestream Support.

---

**Notes:** All formats are supported on Windows. However, Linux currently supports only GXF, QuickTime, MPEG2 Transport Stream, BWAV, and MXF. The initial DIVA release does not support Linux.

---

## AVI (Audio Video Interleaved)

The applicable wrapper format is a single AVI file per object, and may contain audio tracks. This Partial File Restore is supported by AUTO\_DETECT only.

### Adobe Premiere

Supports DVSD and PCM video and audio essences.

### Harris Corporation Nexio 3600

Supports DVSD and PCM video and audio essences.

## AVI with Separate WAV Files

The applicable file format is a single AVI file with separate WAV files. The AVI file contains a single video track, and the WAV files contain a PCM sample format. This Partial File Restore is supported by VIDEO\_FORMAT\_AVI and AUTO\_DETECT in Windows only.

Manufacturer	Product	Release	Supported Video and Audio Essence
Insipiens	AVI Writer	1.0.0.0	MPEG2 LGOP
Matrox	MQSink Filter Format 4	2.0.0.271	DV25, DV50
	MQSink Filter Format 6	2.0.0.271	Dv25, DV50, DVSD
	MQSink Filter for MPEG Format 4	2.0.0.270, 2.0.0.271	MPEG2 LGOP, MPEG2 I-Frame <sup>1</sup>
	DSX AVI File Format 6	1.0.0.362, 1.0.0.401	MPEG2 LGOP <sup>2</sup> , M701 HD

1. MPEG2 I-Frame supported on 2.0.0.271 only.
2. MPEG2 LGOP supported on 1.0.0.362 only.

## AVI with FFV1 or FFVH

AVI clips containing FFV1 or FFVH video essence are supported. Use these formats for video preservation purposes. These codecs are lossless and generate intra-coded frame only (no GOP).

## Avid Interplay Compatibility

The following identifies current Avid Interplay release compatibility for DIVA:

The following are supported for Avid connectivity and Interplay:

- AMC [2.1]: Interplay 2.2 or later: DIVA Core 8.0 or later
- AWD [1.0]: Interplay 3.6 or later: DIVA Core 8.3 or later

## BWAV (Broadcast WAV)

BWAV (Broadcast WAV) is a regular WAV file that includes additional information—Bext and iXML (optional). Bext is a broadcast extension containing metadata, including TimeReference (timecode reference in milliseconds). DIVA Core uses Bext as a timecode reference for Partial File Restore.

BWAV may also contain an optional metadata called iXML. The metadata iXML contains an additional TimeReference and a frame rate. When iXML and Bext are both present, DIVA uses iXML because it contains an accurate frame rate (useful to convert milliseconds to and from a timecode). Without iXML, the millisecond to timecode conversion is only an approximation.

## DIF with Separate WAV Files, and DV with Separate Audio, or Self-contained DV Types

The applicable file format is a single DIF or DV file with separate WAV files, and DV with separate audio or self-contained DV types. WAV files contain the PCM sample format. This Partial File Restore supports Avid Liquid and Omneon Spectrum with DV25 and WAV PCM using either AUTO\_DETECT or VIDEO\_FORMAT\_OMNEON.

## GXF (General Exchange Format)

GXF Partial File Restore is supported in the following formats:

Type	Formats
Aurora Edit	MPEG2 D10 MPEG2 I-frame MPEG2 D10 MPEG2 LGOP
BitScream	DV25
K2 Media System	MPEG2 D10 MPEG2 I-frame MPEG2 D10 MPEG2 LGOP
K2 Media System / Summit	AVC-I DVCPRO XDCAM HD
Mseries	MPEG2 D10 MPEG2 I-frame MPEG2 LGOP

Type	Formats
NewsEdit	DV25 DV50 MPEG2 D10 MPEG2 I-frame
PDR	MJPEG
Profile XP	DV25 DV50 MPEG2 D10 MPEG2 I-frame

## LXF (Leitch Exchange Format)

LXF (Leitch Exchange Format) is well defined, and Partial File Restore supports specific releases of the file format regardless of the source of the clip (Nexio, Flip Factory, and so on). The supported job format is either AUTO\_DETECT or VIDEO\_FORMAT\_LEITCH.

The LXF Release 0 supported video and audio essences are:

- MPEG2 I-frame Standard Definition (SD)
- MPEG2 LGOP SD
- DV
- DVCPRO
- DVCPRO50

The LXF Release 1 supported video and audio essences are:

- MPEG2 4:2:2 (1080i and SD only)
- DV SD
- DVCPRO SD
- DVCPRO50 SD
- DVCPRO HD

## MXF (Material Exchange Format)

MXF standard specification (SMPTE377M) defines multiple operational patterns. Only OP1a is supported. MXF Partial File Restore is supported on Windows and Linux in the following video essence formats:

- DV25, DV50, DV100
- DVCPRO (SD and HD)
- DNxHD

- MPEG2 D10<sup>1</sup>
- MPEG2 LGOP (SD and HD)
- SONY XDCAM HD
- H.264/MPEG-4 AVC
- AVC-Intra (subset of H.264)
- SONY XACV (subset of H264, HD and 4K)
- DNxHR (new codec from AVID for high definition)

---

**Note:** Although these video formats are supported, qualifications are still required because there might be many variations of MXF wrapper for a given video essence format.

---

For Windows, BMX is the default library. You can use MOG SDK only for temporary compatibility.

1. In the DIVA Web App, browse to *Configuration > System Settings > Actors > Edit Actors > Partial Restore Settings*.
2. Click the down arrow for *MXF*.
3. Under the settings, change the *Use BMX Library* parameter to *off* using the slider.

## QuickTime/MP4

QuickTime is a file wrapper and may contain multiple tracks of various types (audio, video, and so on). QuickTime self-contained clips are supported using OMNEON and AUTO\_DETECT.

QuickTime Partial File Restore is supported by Windows Actors only.

Partial File Restore support for QuickTime with MPEG2 LGOP (XDCAM HD 422 with sixteen tracks of audio) is supported as follows, regardless of the type of video or audio content:

- The number of tracks per clip is currently limited to thirty.
- Tracks must have the same duration and start time.
- QuickTime standards support advanced edit list features that are not supported by Partial File Restore.
- Each track must be composed of a single valid edit list entry that may or may not start from zero.

---

1. MXF generated by Seachange are supported as standalone MXF files (no .pd or .vix file).

Some content types are not supported, including some video and audio combinations. The following table identifies supported types:

Supported Track Types	Cardinality
Video	One video track per clip
Video	Two video tracks per clip <sup>1</sup>
Audio	Zero or multiple tracks per clip
Closed Caption <sup>2</sup>	One track per clip
Timecode with a single entry	One track per clip
Timecode with multiple entries	One track per clip

1. When a QuickTime clip contains two video tracks, the tracks must be synchronized and have the same duration and start from 00:00:00:00.
2. Empty Closed Caption tracks are supported.

### QuickTime Self-Contained Clips

The format of the video essence is not a criterion in QuickTime Self-Contained clips. In theory, the Partial File Restore for QuickTime should be able to support any type of video essence. Partial File Restore is not recommended for the following variations in the video essence format:

- Where the video quality supports 420 or 422
- Where the number of pixels is not a factor
- Where the clip is bit rate independent

The following table describes what has already been tested and does not guarantee that Partial File Restore will support it. The only supported audio formats are AIFF and WAV (LPCM).

Manufacturer	Product	Release	Supported Video Essence
Dalet			DVCPRO100
Omneon	Spectrum	5.x	DV25, DVCPRO, DVCPRO50, DVCPRO HD, MPEG2 D10, MPEG2 I-Frame, MPEG2 LGOP, MPEG2 LGOP HD
Oracle	SAMMA solo	Unknown	DV25

### MP4 Clips

MP4 wrapper is also known as MPEG-4 Part 14. This format has been developed based on QuickTime specifications. All the formats currently supported by the QuickTime partial restore are also supported with MP4.



## Supported Unmanaged Storage Repositories

DIVA transfers content to and from external equipment such as broadcast video servers, video editing systems, and generic computer systems. The following are the certified interfaces and protocols supported by DIVA.

---

**Note:** In DIVA versions through DIVA 8.1, *Unmanaged Storage Repositories* were called *Source Destination*.

---

### Unmanaged Storage Repositories

The following table identifies the source and target servers supported by DIVA.

Manufacturer	Server Model	Protocol	Unicode Support
Avid Airspace	See FTP_STANDARD table.	FTP	See the Avid Connectivity and Tools Guide.
Avid Interplay	ISIS or NEXIS	AVID_DHM AVID_DET AVID_AMC AVID_DIRECT	Yes, currently for AMC only.
DataExpedition	Expedat 1.15, Expedat 1.16	MTP	Yes
Dell PowerScale	Isilon	SMB	Yes
Disk (Local)	Internal disk	Direct	Yes
Disk (Network)	Shared File System, SAN, NAS	CIFS	Yes
EVS	Little Big Server, XT3	FTP	No
Grass Valley	NewsEdit, NewsFTP (Aurora Edit HD), UIM Gateway with MXF <sup>1</sup> , K2 <sup>2</sup>	FTP	Only K2 is supported.
Leitch	VR Series <sup>3</sup> , Nexio 3600	FTP	Only Nexio 3600 is supported.
Omneon	Spectrum 4.6 SR2 Spectrum 4.7 SR2 Spectrum 5.0 SR1	FTP and AVI player FTP and AVI Player FTP and AVI Player	Only Spectrum 5.0 SR1 is supported.

<b>Manufacturer</b>	<b>Server Model</b>	<b>Protocol</b>	<b>Unicode Support</b>
Omneon	Spectrum 6.1 with System Manager 5.14	FTP Only	Yes
Omneon	MediaGrid <sup>4</sup> 1.1	Mapped drive using MediaGrid file system drivers	Yes
Quantel	SQserver regional server with ISA gateway <sup>5</sup>	FTP	No
Sony	News Base Hyper Agent	FTP	No
Various (UNIX, Windows, Mac)	Any standard FTP server (RFC-959)	FTP	No
	Secure FTP server V3 (limited support)	SFTP	No

1. UIM Gateway with MXF is supported for release 2.0.6.3.
2. GXF and MXF formats are supported.
3. Supported only using WanStreamer or ArchiveStreamer.
4. Linux does not support MediaGrid because the API it depends on is not Linux compatible. MXF supports release 2.1-22.09. Release 2.1-22.10 supports intelligent archive in TAR format.
5. SQserver regional server with ISA gateway

The following table identifies FTP servers supporting FTP\_STANDARD.

<b>Manufacturer</b>	<b>Product Name</b>	<b>Core Actor Qualified</b>	<b>Unicode Support</b>	<b>WFM Qualified</b>	<b>OTU Qualified</b>
Microsoft	IIS	Yes <sup>1</sup>	No	Yes <sup>2</sup>	Yes
FileZilla	FileZilla FTP Server	Yes	Yes	No	Yes
Gene6	Gene6 FTP Servers	Yes	Yes	No	No

1. Actor supports IIS with UNIX-like listing type configured.
2. WFM supports IIS with DOS-like listing type configured.

## Supported Transcoders

DIVA supports the use of Vantage for performing transcoding operations. The following table lists the DIVA version and the qualified versions of Vantage:

DIVA Version	Vantage Version
DIVA 7.1	4.1
DIVA 7.2	6.2
DIVA 7.3	6.3
DIVA 7.4	6.3
DIVA 7.5	7.1
DIVA 7.6	7.1
DIVA 7.7	8.1
DIVA 8.0	8.1
DIVA 8.1	8.1
DIVA 8.2	8.1
DIVA 8.3	8.1
DIVA 9.0	8.1
DIVA 9.1	8.1
DIVA 9.2	8.1
DIVA 9.3	8.1

## Supported Avid Environments

DIVA supports Avid Connectivity and MediaCentral Asset Management DIVA Connector version 4.6.0.

For detailed information see *The AVID Connectivity and Avid for DIVA Applications* in the *DIVA User Guide*.

## MediaCentral Compatibility

The MediaCentral | Asset Management DIVA Connector version 4.6.0 is now tested and qualified with DIVA. This means DIVA and this DIVA Connector release can be updated if it is not release 4.6.0, and then all the releases of MediaCentral listed can be supported.

This new connector release can be used in the following MediaCentral | Asset Management systems:

<b>MC   AM Release Date</b>	<b>AM Build Number</b>
2019.6	7.2
2019.9	7.3
2020.4	7.4
2020.9	7.5
2021.3	7.6
2021.7	7.7
2021.11	8.0
2022.3	8.0.1
2022.12	8.1
2023.7	8.1
2024	8.2, 8.3, and 9.3